

CERTIFICATE

TÜV NORD CERT GmbH
herewith declares that

Lepton Solar (Changshu) Co., Ltd.
No. 9, Sunshine Avenue, Yushan High Technology Industry Zone,
Changshu City, Jiangsu Province, 215500
P.R. China

is authorized to provide the product mentioned below with the mark as illustrated:

Description of product (details see Annex 2):

Crystalline Silicon Terrestrial Photovoltaic (PV) Modules



Valid from: 2024-07-23
Valid until: 2025-01-02

Certification program:	P12-VA-01 Rev. 17 09.20
Certification fundamental(s):	IEC 62716:2013 / EN 62716:2013.
Registered No.:	44 780 20 406749 - 006R4A1M4
Manufacturer and factory(-ies):	See Annex 1
Test Report No.:	492011340.005
File No.:	PVP01197/24P-02



TÜV NORD CERT GmbH
Certification Body
Consumer Products



Essen, 2024-07-23

Please also pay attention to the information stated overleaf.

Manufacturer and factory(-ies):

Manufacturer: **Lepton Solar (Changshu) Co., Ltd.**
No. 9, Sunshine Avenue, Yushan High Technology Industry Zone,
Changshu City
Jiangsu Province, 215500, P.R. China

Factory: **Lepton Solar (Changshu) Co., Ltd.**
No. 9, Sunshine Avenue, Yushan High Technology Industry Zone,
Changshu City
Jiangsu Province, 215500, P.R. China

Factory inspection report no.: 862010379.007

Remark:

Factory inspection is mandatory to be performed annually. Please refer to factory inspection report for detailed information.



TÜV NORD CERT GmbH
Certification Body
Consumer Products

Description of product(s):

Module types:	PV Modules with 6" Half Cut Mono-crystalline Silicon Solar Cells: 144 cells: LP158*158-M-72-H-***W (***) = 365-400, in increment of 5) 132 cells: LP158*158-M-66-H-***W (***) = 335-365, in increment of 5) 120 cells: LP158*158-M-60-H-***W (***) = 305-330, in increment of 5) 144 cells: LP158*158-M-72-MH-***W (***) = 390-410, in increment of 5) 132 cells: LP158*158-M-66-MH-***W (***) = 360-375, in increment of 5) 120 cells: LP158*158-M-60-MH-***W (***) = 325-340, in increment of 5) 144 cells: LP166*166-M-72-MH-***W (***) = 420-455, in increment of 5) 132 cells: LP166*166-M-66-MH-***W (***) = 385-415, in increment of 5) 120 cells: LP166*166-M-60-MH-***W (***) = 350-380, in increment of 5)
Maximum system voltage:	1500V
Fuse rating:	15A or 20A
Application class:	Class A
Electrical protection class:	Class II
Module types:	PV Modules with 6" Half Cut Poly-crystalline Silicon Solar Cells: 144 cells: LP156*156-P-72-H-***W (***) = 335-370, in increment of 5) 120 cells: LP156*156-P-60-H-***W (***) = 280-305, in increment of 5)
Maximum system voltage:	1500V
Fuse rating:	15A
Application class:	Class A
Electrical protection class:	Class II



TÜV NORD CERT GmbH
Certification Body
Consumer Products

Module types: **PV Modules with 7" Half Cut Mono-crystalline Silicon Solar Cells:**
156 cells: LP182*182-M-78-MH-***W (** = 560-605, in increment of 5)
144 cells: LP182*182-M-72-MH-***W (** = 515-555, in increment of 5)
132 cells: LP182*182-M-66-MH-***W (** = 475-510, in increment of 5)
120 cells: LP182*182-M-60-MH-***W (** = 430-465, in increment of 5)
108 cells: LP182*182-M-54-MH-***W (** = 390-415, in increment of 5)

Maximum system voltage: 1500V

Fuse rating: 25A

Application class: Class A

Electrical protection class: Class II

Module types: **PV Modules with Half-cut 210*210mm Mono-crystalline Silicon Solar Cells:**

132 cells: LP210*210-M-66-MH-***W (** = 630-670, in increment of 5)

120 cells: LP210*210-M-60-MH-***W (** = 575-610, in increment of 5)

108 cells: LP210*210-M-54-MH-***W (** = 515-545, in increment of 5)

96 cells: LP210*210-M-48-MH-***W (** = 460-485, in increment of 5)

84 cells: LP210*210-M-42-MH-***W (** = 400-425, in increment of 5)

110 cells: LP210*210-M-55-MH-***W (** = 520-555, in increment of 5)

100 cells: LP210*210-M-50-MH-***W (** = 475-505, in increment of 5)

90 cells: LP210*210-M-45-MH-***W (** = 425-455, in increment of 5)

80 cells: LP210*210-M-40-MH-***W (** = 380-400, in increment of 5)

Maximum system voltage: 1500V

Fuse rating: 30A

Application class: Class A

Electrical protection class: Class II



TÜV NORD CERT GmbH
Certification Body
Consumer Products

Module types:	PV Modules with Half-cut 182*182/188mm n-type TOPCon Bifacial Silicon Solar Cells: 156 cells: LP182*182-M-78-NH-***W (***) = 580-625, in increment of 5) 144 cells: LP182*182-M-72-NH-***W (***) = 555-600, in increment of 5) 132 cells: LP182*182-M-66-NH-***W (***) = 510-550, in increment of 5) 120 cells: LP182*182-M-60-NH-***W (***) = 460-500, in increment of 5) 108 cells: LP182*182-M-54-NH-***W (***) = 410-450, in increment of 5)
Maximum system voltage:	1500V
Fuse rating:	25A
Application class:	Class A
Electrical protection class:	Class II

Module types:	PV Modules with Half-cut 182*210mm n-type TOPCon Bifacial Silicon Solar Cells: 132 cells: LP182*210-M-66-NH-***W (***) = 580-635, in increment of 5) 120 cells: LP182*210-M-60-NH-***W (***) = 530-575, in increment of 5) 108 cells: LP182*210-M-54-NH-***W (***) = 475-520, in increment of 5) 96 cells: LP182*210-M-48-NH-***W (***) = 420-460, in increment of 5)
Maximum system voltage:	1500V
Fuse rating:	25A
Application class:	Class A
Electrical protection class:	Class II

Module types:	PV Modules with Half-cut 182*199/191mm n-type TOPCon Bifacial Silicon Solar Cells: 144 cells: LP182*199-M-72-NH-***W (***) = 570-655, in increment of 5) 132 cells: LP182*199-M-66-NH-***W (***) = 525-600, in increment of 5) 120 cells: LP182*199-M-60-NH-***W (***) = 475-545, in increment of 5) 108 cells: LP182*199-M-54-NH-***W (***) = 430-490, in increment of 5)
Maximum system voltage:	1500V
Fuse rating:	25A
Application class:	Class A
Electrical protection class:	Class II



TÜV NORD CERT GmbH
Certification Body
Consumer Products

Module types:

PV Modules with Half-cut 210*210mm n-type TOPCon Bifacial Silicon Solar Cells:

132 cells: LP210*210-M-66-NH-***W (** = 675-700, in increment of 5)

120 cells: LP210*210-M-60-NH-***W (** = 615-635, in increment of 5)

108 cells: LP210*210-M-54-NH-***W (** = 555-570, in increment of 5)

96 cells: LP210*210-M-48-NH-***W (** = 490-510, in increment of 5)

84 cells: LP210*210-M-42-NH-***W (** = 430-445, in increment of 5)

Maximum system voltage: 1500V

Fuse rating: 30A

Application class: Class A

Electrical protection class: Class II

Remark:

For detailed product information, please refer to CDF (Constructional Data Form).




TÜV NORD CERT GmbH
Certification Body
Consumer Products

CERTIFICATE

TÜV NORD CERT GmbH
herewith declares that

Lepton Solar (Changshu) Co., Ltd.
No. 9, Sunshine Avenue, Yushan High Technology Industry Zone,
Changshu City, Jiangsu Province, 215500
P.R. China

is authorized to provide the product mentioned below with the mark as illustrated:




Description of product (details see Annex 2):

Crystalline Silicon Terrestrial Photovoltaic (PV) Modules

Certification program:	P12-VA-01 Rev. 17 09.20
Certification fundamental(s):	IEC 62716:2013 / EN 62716:2013 + AC:2014.
Registered No.:	44 780 23 406749 - 234
Manufacturer:	see Annex 1
Test Report No.:	492012602.001
File No.:	PVP04137/23P-06

Valid until: 2028-07-30



TÜV NORD CERT GmbH
Certification Body
Consumer Products

Essen, 2023-07-31

Please also pay attention to the information stated overleaf.

Module types:

Double Glass PV Modules with half-cut 7" n-type TOPCon Bifacial Mono Solar Cells:

156 cells: LP182*182-M-78-NB-***W (***) = 580-625, in increment of 5)

144 cells: LP182*182-M-72-NB-***W (***) = 555-605, in increment of 5)

132 cells: LP182*182-M-66-NB-***W (***) = 510-555, in increment of 5)

120 cells: LP182*182-M-60-NB-***W (***) = 460-505, in increment of 5)

108 cells: LP182*182-M-54-NB-***W (***) = 410-450, in increment of 5)

Maximum system voltage:

1500V

Fuse rating:

25A or 30A

Application class:

Class A

Electrical protection class:

Class II

Module types:

Double Glass PV Modules with half-cut 8" n-type TOPCon Bifacial Mono Solar Cells:

132 cells: LP210*210-M-66-NB-***W (***) = 675-705, in increment of 5)

120 cells: LP210*210-M-60-NB-***W (***) = 615-640, in increment of 5)

108 cells: LP210*210-M-54-NB-***W (***) = 555-575, in increment of 5)

96 cells: LP210*210-M-48-NB-***W (***) = 490-510, in increment of 5)

84 cells: LP210*210-M-42-NB-***W (***) = 430-445, in increment of 5)

Maximum system voltage:

1500V

Fuse rating:

30A or 35A

Application class:

Class A

Electrical protection class:

Class II

Remark:

For detailed product information, please refer to CDF (Constructional Data Form) in Annex 1 of test report.



TÜV NORD CERT GmbH
Certification Body
Consumer Products

Description of product(s):

Module types:

Double Glass PV Modules with 7" Half Cut Mono-crystalline Silicon Solar Cells:

144 cells: LP182*182-M-72-MB-***W (***) = 520-550, in increment of 5)

132 cells: LP182*182-M-66-MB-***W (***) = 475-505, in increment of 5)

120 cells: LP182*182-M-60-MB-***W (***) = 435-455, in increment of 5)

108 cells: LP182*182-M-54-MB-***W (***) = 390-410, in increment of 5)

Maximum system voltage:

1500V

Fuse rating:

25A

Application class:

Class A

Electrical protection class:

Class II

Module types:

Double Glass PV Modules with 8" Half Cut Mono-crystalline Silicon Solar Cells:

132 cells: LP210*210-M-66-MB-***W (***) = 630-670, in increment of 5)

120 cells: LP210*210-M-60-MB-***W (***) = 575-610, in increment of 5)

108 cells: LP210*210-M-54-MB-***W (***) = 515-545, in increment of 5)

96 cells: LP210*210-M-48-MB-***W (***) = 460-485, in increment of 5)

84 cells: LP210*210-M-42-MB-***W (***) = 400-425, in increment of 5)

110 cells: LP210*210-M-55-MB-***W (***) = 520-555, in increment of 5)

100 cells: LP210*210-M-50-MB-***W (***) = 475-505, in increment of 5)

90 cells: LP210*210-M-45-MB-***W (***) = 425-455, in increment of 5)

80 cells: LP210*210-M-40-MB-***W (***) = 380-400, in increment of 5)

Maximum system voltage:

1500V

Fuse rating:

30A or 35A

Application class:

Class A

Electrical protection class:

Class II



TÜV NORD CERT GmbH
Certification Body
Consumer Products

Module types: **Double Glass PV Modules with half-cut 7" n-type TOPCon Bifacial Mono Solar Cells:**
156 cells: LP182*182-M-78-NB-***W (***) = 580-625, in increment of 5)
144 cells: LP182*182-M-72-NB-***W (***) = 555-605, in increment of 5)
132 cells: LP182*182-M-66-NB-***W (***) = 510-555, in increment of 5)
120 cells: LP182*182-M-60-NB-***W (***) = 460-505, in increment of 5)
108 cells: LP182*182-M-54-NB-***W (***) = 410-450, in increment of 5)

Maximum system voltage: 1500V
Fuse rating: 25A or 30A
Application class: Class A
Electrical protection class: Class II

Module types: **Double Glass PV Modules with half-cut 8" n-type TOPCon Bifacial Mono Solar Cells:**
132 cells: LP210*210-M-66-NB-***W (***) = 675-705, in increment of 5)
120 cells: LP210*210-M-60-NB-***W (***) = 615-640, in increment of 5)
108 cells: LP210*210-M-54-NB-***W (***) = 555-575, in increment of 5)
96 cells: LP210*210-M-48-NB-***W (***) = 490-510, in increment of 5)
84 cells: LP210*210-M-42-NB-***W (***) = 430-445, in increment of 5)

Maximum system voltage: 1500V
Fuse rating: 30A or 35A
Application class: Class A
Electrical protection class: Class II

Remark:

For detailed product information, please refer to CDF (Constructional Data Form) in Annex 1 of test report.



TÜV NORD CERT GmbH
Certification Body
Consumer Products